

Material & Finish:
1 Body: brass, albaloy plated
2 Center contact: phosphor bronze, silver plated
3 Insulator: PTFE

Environmental Data:
1 Temperature range: -55℃~+125℃
2 2011/65/EU(RoHS) and 2015/863/(RoHS): Compliant
3 (EC) No 1907/2006(REACH): Compliant

Electrical Specifications:
1 Impedance: 50 Ω
2 Frequency range: DC~3 GHz
3 VSWR: 1.25 max.

Revisions			
Rev.	Description	Date	Approved
A	Initial Release	10/15/26	JQ





CABLE STRIPPING DIMENSIONS

NOTE: Specifications are subject to change without notice.
Contact us for the latest data before finalizing your design.

Drawn	WY	Date	10/15/26
Checked	XY	Date	10/15/26
Approved	JQ	Date	10/15/26

Unless otherwise specified dimensions are in millimeters, dimensions in [ ] are in inches for customer reference only unless otherwise specified tolerance are:

.XX	±0.13 [.005"]
.X	±0.20 [.008"]
X	±0.50 [.019"]
.X°	±1°
X°	±2°

These drawings and specifications are the property of Anoison. They shall not be reproduced or used without written permission. © 2026 Anoison. All rights reserved.

ANOISON

Title: N straight female clamp for 1/2" super flex cable

View

Part No.: ANO 5112-2449

Size	Scale	Sheet	Rev.
A3	5:1	1/1	A