
Material & Finish:
1 Body: Brass, Albaloy
2 Center contact: Beryllium copper alloy, Gold plated
3 Insulator: PEI
4 Coupling nut: Brass, Albaloy

Environmental Data:
1 Temperature range: -55℃~+125℃
2 2011/65/EU(RoHS) and 2015/863/(RoHS): Compliant
3 (EC) No 1907/2006(REACH): Compliant

Electrical data:
1 Impedance: 50 Ω
2 Frequency range: DC~18 GHz
3 VSWR: 1.15 max.
4 Average power: 2 w average to 25°c ambient temperatrue, derated linearly to 0.2 w @ 125°c
5 Peak power: 250 kw (5μs pluse width with 0.8% duty cycle)

Revisions			
Rev.	Description	Date	Approved
A	Initial release	09/04/26	JQ



NOTE: Specifications are subject to change without notice.
Contact us for the latest data before finalizing your design.

Drawn: XY	Date: 09/04/26	ANOISON
Checked: XW	Date: 09/04/26	
Approved: JQ	Date: 09/04/26	Title: Coaxial termination, N male, 2 watts, DC~18GHz

Unless otherwise specified dimensions are in millimeters, dimensions in [ ] are in inches for customer reference only unless otherwise specified tolerance are:

.XX	±0.13 [.005"]
.X	±0.20 [.008"]
X	±0.50 [.019"]
.X°	±1°
X°	±2°

These drawings and specifications are the property of Anoison. They shall not be reproduced or used without written permission. © 2026 Anoison. All rights reserved.

View	Part No.			
	ANO 751-187			
	Size: A3	Scale: 2.5:1	Sheet: 1/1	Rev.: A